PT78HT200 Series

2 Amp Positive Step-Down Integrated Switching Regulator

Power Trends Products from Texas Instruments

SLTS057B

(Revised 10/15/2000)

- High Efficiency: Up to 90%
- Wide Input Range
- Self-Contained Inductor
- Short-Circuit Protection
- Over-Temperature Protection
- Fast Transient Response

The PT78HT200 is a series of fixed output, wide-input range, 3-terminal Integrated Switching Regulators (ISRs). These ISRs have a maximum output current of 2A. The output voltage is also laser trimmed for high accuracy. Features include excellent line and load regulation, internal short-circuit and over-temperature protection.

The PT78HT200 series is available in three package outlines, including horizontal SMD. Their small size and output voltage selection makes these regulators ideal for use in a variety of applications.

Standard Application



C1 = Optional 1µF ceramic
C2 = Required 100µF electrolytic (1)

Pin-Out Information

Pin	Function
1	V_{in}
2	GND
3	V_{out}



Pkg Style 500

Ordering Information

PT78HT2 XX Y

Output Voltage
33 = 3.3 Volts
05 = 5.0 Volts
53 = 5.25 Volts
65 = 6.5 Volts
08 = 8.0 Volts

Package Suffix
V = Vertical Mount
S = Surface Mount
H = Horizontal Mount

Specifications

Characteristics (T_a = 25°C unless noted)	Symbols	Conditions		PT78HT200 SERIES Min	Typ	Max	Units
Output Current	I_o	Over V_{in} range		0.1 (2)	—	2.0	A
Short Circuit Current	I_{sc}	V_{in} = V_{in} min		—	6.0	—	Apk
Input Voltage Range	V_{in}	0.1 ≥ I_o ≥ 2.0A	V_o =3.3V V_o =5.0V V_o =6.5V V_o =8.0V	9 9 10.5 12	— — — —	15 28 28 28	V
Output Voltage Tolerance	ΔV_o	Over V_{in} range, I_o = 2.0A T_a = 0°C to +60°C		—	±1.0	±2.0	%Vo
Line Regulation	Reg_{line}	Over V_{in} range		—	±0.4	±0.8	%Vo
Load Regulation	Reg_{load}	0.1 ≤ I_o ≤ 2.0A		—	±0.2	±0.4	%Vo
Vo Ripple/Noise	V_n	V_{in} = V_{in} min, I_o = 2.0A		—	±1	—	%Vo
Transient Response (with 100µF output cap)	t_{tr}	50% load change Vo over/undershoot		—	100 5.0	—	µSec %Vo
Efficiency	η	V_{in}=9V, I_o = 2.0A V_{in} =12V, I_o =2.0A V_{in} =15V, I_o =2.0A	V_o =3.3V V_o =5.0V V_o =8.0V	— — —	80 85 90	— — —	%
Switching Frequency	f_o	Over V_{in} and I_o ranges	V_o ≥5.0V V_o =3.3V	700 950	750 1,000	800 1,050	kHz
Absolute Maximum Operating Temperature Range	T_a	Over V_{in} range		-40	—	+85 (3)	°C
Thermal Resistance	θ_{ja}	Free Air Convection, (40-60LFM)		—	40	—	°C/W
Storage Temperature	T_s	—		-40	—	+125	°C
Mechanical Shock	—	Per Mil-STD-883D, Method 2002.3		—	500	—	G's
Mechanical Vibration	—	Per Mil-STD-883D, Method 2007.2, 20-2000 Hz, soldered in a PC board		—	5	—	G's
Weight	—	—		—	6.5	—	Grams

Notes: (1) The PT78HT200 Series requires a 100µF electrolytic or tantalum output capacitor for proper operation in all applications.
(2) ISR will operate down to no load with reduced specifications.
(3) See Safe Operating Area curves for derating

Typical Characteristics

PT78HT233 3.3 VDC (See Note A)

Efficiency vs Output Current



Ripple vs Output Current



Power Dissipation vs Output Current



Safe Operating Area @V_{in} =12V (Note B)



PT78HT205 5.0 VDC (See Note A)

Efficiency vs Output Current



Ripple vs Output Current



Power Dissipation vs Output Current



Safe Operating Area @V_{in} =15V (Note B)



PT78HT208 8.0 VDC (See Note A)

Efficiency vs Output Current



Ripple vs Output Current



Power Dissipation vs Output Current



Safe Operating Area @V_{in} =15V (Note B)



Note A: *All characteristic data has been developed from actual products tested at 25°C. This data is considered typical data for the ISR.*
Note B: *SOA curves represent operating conditions at which internal components are at or below manufacturer's maximum rated operating temperatures.*

PACKAGING INFORMATION

Orderable Device	Status [1]	Package Type	Package Drawing	Pins	Package Qty	Eco Plan [2]	Lead/Ball Finish	MSL Peak Temp [3]
PT78HT205H	ACTIVE	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT205S	ACTIVE	SIP MOD ULE	EFC	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT205ST	ACTIVE	SIP MOD ULE	EFC	3	200	TBD	Call TI	Level-1-215C-UNLIM
PT78HT205V	ACTIVE	SIP MOD ULE	EFD	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT208H	ACTIVE	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT208S	ACTIVE	SIP MOD ULE	EFC	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT208V	ACTIVE	SIP MOD ULE	EFD	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT233H	ACTIVE	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT233S	ACTIVE	SIP MOD ULE	EFC	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT233V	ACTIVE	SIP MOD ULE	EFD	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT253H	ACTIVE	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT253S	ACTIVE	SIP MOD ULE	EFC	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT253V	ACTIVE	SIP MOD ULE	EFD	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT265H	ACTIVE	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT265S	ACTIVE	SIP MOD ULE	EFC	3	25	TBD	Call TI	Level-1-215C-UNLIM
PT78HT265V	ACTIVE	SIP MOD ULE	EFD	3	25	TBD	Call TI	Level-1-215C-UNLIM

[1] The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

[2] Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.
TBD: The Pb-Free/Green conversion plan has not been defined.
Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.
Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

[3] MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		**Applications**	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
		Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265